





863 Colored Harness Wrap Tape

High quality Soft-PVC-Film, coated with a strong rubber based adhesive, hand applicable, 105°C.

FEATURES:

- Rubber adhesive
- PVC carrier

BENEFITS:

- Black and other colors available
- Highly conformable
- Flame resistant
- · Controlled, even unwind
- Meet RoHS & REACH



STANDARD SIZES:

Length:18m, 25m Width: 19mm, 25mm Core ID: 32mm, 38mm

COLORS:

Black White Yellow Red Blue Green

Other sizes and colors are available on request.





863

Properties	Value	Unit	Test Method	
Total thickness	0.100±0.015	mm	EN 1942	
Tensile strength	≥14	N/cm	ISO 29864	
Elongation at break	≥100	%	ISO 29864	
Adhesion strength			ISO 29862	
— to steel	≥1.5	N/cm		
— to backing	≥1.5	N/cm		
Unwind force	1.5~4.0	N/cm	EN 1944	
Flammability	B(self-extinguishing)		ISO 3795	
Dielectric Strength	≥40	kV/mm	IEC 60454	
Temperature rating	B:-25~105	$^{\circ}$ C	GMW 16740	

Note: The listed values are required only and not intended to serve as product specifications

RECOMMENDED USES:

Use as permanent wrapping on wiring harness agricultural equipment, aircraft, aerospace and electronic assemblies. Preferred when requirements include need for numerous colors plus long term reliability under varying and extreme environmental conditions.

STORAGE AND SHELF LIFE

The shelf life of the product is five years when stored at 20-30°C, max 65% relative humidity and out of direct sunlight, in original packaging.

Please refer to www.yongletape.com.cn for complete terms and conditions, including warranty terms, relating to this product. You should periodically review the site as terms and conditions are subject to change without notice.

© 2018 Avery Dennison Corporation. All rights reserved. Avery Dennison Yongle is trademark of Avery Dennison Corporation. Plyon and all other Avery Dennison brands, product names or service programs are trademarks of Avery Dennison Corporation.



